

66

# FIREBOX T35-R

Up to 940 Mbps firewall throughput, 5 x 1Gb ports, 25 branch office VPNs

## RUGGEDIZED SECURITY FOR HARSH ENVIRONMENTS

Traditional firewalls are designed for office environments or rack-mounted in a climate-controlled server room, where issues with temperature, water and dust are negligible. Initiatives to connect and modernize industrial operations require a device that can withstand these conditions, ensure effective security as part of WatchGuard's Unified Security Platform<sup>®</sup>, and deliver consistently high performance. As an IP64-rated device, Firebox T35-R is the highest-performing industrially hardened compact security appliance available.

WatchGuard Firebox T35-R allowed us to extend the security protections we rely on at our office, to our remote locations, without having to worry about device failure and downtime as the result of environmental conditions.

#### **BUILT TO WITHSTAND HARSH CONDITIONS**

Dust, moisture, and extreme temperatures can dramatically reduce the lifecycle and performance of network hardware. Firebox T35-R features an IP64-rated industrial enclosure that is both dust and splash proof, and capable of operating in temperatures of -40° to +60° C (-40° to +140° F). The ruggedized construction of Firebox T35-R means you can deploy the appliance in harsh environments without needing to build a special enclosure.

#### ZERO-TOUCH REMOTE DEPLOYMENT

With Firebox T35-R you can avoid sending your team to every location a device is needed. Our Cloud-based RapidDeploy technology allows you to create and store Firebox configuration data in the Cloud and have an appliance directly shipped to its destination. Once the device arrives, a user only need plug it in – RapidDeploy will automatically download and apply your pre-determined configuration.

### EASY TO MANAGE AND UNDERSTAND

Firebox T35-R is not only easy to initially configure and deploy, it is designed with an emphasis on centralized management, making ongoing policy and network management across your distributed environment simple and straightforward. WatchGuard Cloud provides a suite of big data visibility and reporting tools that instantly identify and distill key network security threats, issues and trends so you can take immediate preventive or corrective action. Security is complex, running it doesn't have to be.

### LAYERED SECURITY FOR INDUSTRIAL USE CASES

While connecting remote locations and industrial environments can help you achieve a higher level of operational efficiency, the security implications of doing so can be severe. Breaches of industrial control systems (ICS) can have significant impact, bringing your business to a halt and even potentially endangering lives. Firebox T35-R includes specific SCADA IPS signatures to protect against well-known exploits of common industrial control systems (ICS), making it an ideal choice for remote locations with ICS security needs.

#### **FEATURES & BENEFITS**

- IP64-rated industrial enclosure is dust and splash proof, and capable of operating in temperatures of -40° to +60° C (-40° to +140° F).
- All logging and reporting functions included with purchase, with over 100 dashboards and reports including PCI and HIPAA.
- 5 Gigabit Ethernet ports support high-speed LAN backbone infrastructures & gigabit WAN connections.
- Variable DC power from 12 to 48 V with optional AC power supply.
- SCADA IPS signatures to protect against well-known exploits of common industrial control systems.
- DIN rail included.



Firebox T35-R	TECHNICAL SPECIFICATIONS		
THROUGHPUT <sup>1</sup>			
UTM (full scan) <sup>2</sup>	203 Mbps		
Firewall (IMIX)	480 Mbps		
VPN (IMIX)	96 Mbps		
HTTPS (IPS enabled, full scan)	151 Mbps		
Antivirus	325 Mbps		
IPS (full scan)	300 Mbps		
Firewall (UDP 1518)	940 Mbps		
VPN (UDP 1518)	560 Mbps		
CAPACITY	·		
Interfaces 10/100/1000	5		
I/O interfaces	1 Serial/2 USB		
Concurrent connections	1.3 M		
Concurrent connections (proxy)	135,000		
New connections per second			
•	6,800		
VLANs	50		
WSM licenses (incl)	0		
TDR Host Sensors included	20		
VPN TUNNELS			
Branch Office VPN	25		
Mobile VPN	25		
SECURITY FEATURES			
Firewall	Stateful packet inspection, TLS decryption, proxy firewall		
Application proxies	HTTP, HTTPS, FTP, DNS, TCP/UDP, POP3S, SMTPS, IMAPS and Explicit Proxy		
Threat protection	DoS attacks, fragmented & malformed packets, blended threats		
Filtering options	Browser Safe Search, Google for Business		
VPN			
Site to Site VPN	IKEv2, IPSec, Policy and Route Based Tunnels, TLS hub and spoke		
Remote Access VPN	IKEv2, IPSec, L2TP, TLS		
VISIBILITY			
Logging and notifications	WatchGuard Cloud & Dimension, Syslog, SNMP v2/v3		
	WatchGuard Cloud to Dimension, Systeg, Stown v2/VS WatchGuard Cloud includes over 100 pre-defined		
Reporting	reports, executive summary and visibility tools		
CERTIFICATIONS			
Security	Pending: CC EAL4+, FIPS 140-2		
Safety	NRTL/CB		
Network	IPv6 Ready Gold (routing)		
Hazardous substance control	WEEE, RoHS, REACH		
NETWORKING			
SD-WAN	Multi-wan failover, dynamic path selection, jitter/ loss/latency measurement		
Dynamic Routing	RIP, OSPF, BGP		
High Availability	Active/passive, active/active		
	•		
QoS	802.1Q, DSCP, IP Precedence		
Traffic Management	By policy or application		
IP address assignment	Static, DHCP (server, client, relay), PPPoE, DynDNS		
NAT	Static, dynamic, 1:1, IPSec traversal, policy-based		
Link aggregation	802.3ad dynamic, static, active/backup		
Link aggregation	ERNATIONAL SALES +1.206.613.0895		

WEB www.watchguard.com



DC

USB Reset Network Interface Power Switch

PHYSICAL AND POWER SPECIFICATIONS

Product Dimensions	9.5" x 2.6" x 1.7" (240.6	9.5" x 2.6" x 1.7" (240.6 x 66 x 43.3mm)			
Shipping Dimension	11.77" x 9.84" x 3.74" (2	11.77″ x 9.84″ x 3.74″ (29.9 x 25 x 9.5 cm)			
Shipping Weight	4.96 lbs (2.25 kg)	4.96 lbs (2.25 kg)			
Power Consumption	12 V, 15W (max)	12 V, 15W (max)			
Power	100-240 VAC Autosens optional accessory	100-240 VAC Autosensing AC Power Supply is available as optional accessory			
ENVIRONMENT	OPERATING	STORAGE			
Temperature	-40° F to 140° F -40° C to 60° C	-40° F to 158° F -40° C to 70° C			
Relative Humidity	10% to 85% non-condensing	10% to 85% non-condensing			
Altitude	0 to 9,843 ft at 95° F (3,000 m at 35° C)	0 to 15,000 ft at 95° F (4,570 m at 35° C)			
MTBF	83,182 hours @ 140° F	83,182 hours @ 140° F (60° C)			

#### **STRONG SECURITY AT EVERY LAYER**

Uniquely architected to be the industry's smartest, fastest, and most effective network security products, WatchGuard solutions deliver in-depth defenses against advanced malware, ransomware, botnets, trojans, viruses, drive-by downloads, data loss, phishing and much more. Total and Basic Security Suite packages are available on all Firebox solutions.

	SUPPORT	BASIC SECURITY	TOTAL SECURITY
Stateful Firewall	1	1	1
VPN	$\checkmark$	$\checkmark$	1
SD-WAN	1	$\checkmark$	1
Access Portal*	$\checkmark$	$\checkmark$	1
Intrusion Prevention Service (IPS)		$\checkmark$	1
Application Control		$\checkmark$	1
WebBlocker		1	1
spamBlocker		$\checkmark$	1
Gateway AntiVirus		$\checkmark$	1
Reputation Enabled Defense		$\checkmark$	1
Network Discovery		1	1
APT Blocker			1
Threat Detection & Response			1
DNSWatch			1
IntelligentAV**			1
WatchGuard Cloud Visibility Data Retention		1 Day	30 Days
Support	Standard (24 x 7)	Standard (24 x 7)	Gold (24 x 7)

\*Not available on Firebox T15/T15-W, T20/T20-W, or T35-R. Total Security Suite required for M270, M370, M470, M570, M670.

\*Not available on Firebox T15/T15-W, T20/T20-W, or T35-R.

## For details, talk to your authorized WatchGuard reseller or visit www.watchguard.com.

<sup>1</sup>Throughput rates are determined using multiple flows through multiple ports and will vary depending on environment and configuration. Max firewall throughput tested via direct connection using 1518 byte UDP frame based on RFC 2544 methodology. All testing performed on Fireware version 12.5.1.

<sup>2</sup>UTM throughput is measured using HTTP traffic with AV, IPS, and Application Control enabled, and does not account for all security services available on the appliance.

No express or implied warranties are provided for herein. All specifications are subject to change and expected future products, features or functionality will be provided on an if and when available basis. © 2020 WatchGuard Technologies, Inc. All rights reserved. WatchGuard, the WatchGuard logo, Firebox, Fireware, DNSWatch, and IntelligentAV are trademarks or registered trademarks of WatchGuard Technologies, Inc. in the United States and/or other countries. All other trademares are the property of their respective owners. Part No. WGCE67207\_120820